

# ZCAT

*Compact Size,  
Big Time Results.*



## Specifications

**Engine Options:**

- 16hp Honda, air-cooled, twin cylinder, vertical shaft
- 17hp Kawasaki, air-cooled, twin cylinder, vertical shaft
- 19hp Kawasaki, air-cooled, twin cylinder, vertical shaft

**Fuel Capacity/Design:**

6 gallons, dual fuel tanks with molded-in cupholder.

**Travel Control:**

Twin "Quick-Fit" steering controls with gas dampers for smooth, precise maneuverability. Adjustable to fit various operator sizes.

**Ground Speed:**

7.5mph forward, 5.5mph reverse

**Main Frame Construction:**

Steel tube frame, full length, fully welded

**Drive Tires:**

- 36": 23 x 8.5 -12, 4 ply
- 42": 23 x 9.5 -12, 4 ply

**Caster Tires:**

11 x 4 - 5, 4 ply; Flat-Free, semi-pneumatic

**Caster Wheel Bearings:**

Tapered roller bearings

**Front Caster Arm Design:**

Bolt-on for easy replacement if necessary

**Hydraulic Pumps:**

Dual Pumps; 10cc displacement, Hydro-Gear BDP-10A

**Hydraulic Oil Cooler:**

Not required - Aluminum hydraulic tank with cooling fins

**Hydraulic Oil Filter:**

10 micron

**Hydraulic Wheel Motors:**

Dual Hydro-Gear cast-iron high torque motors

**Electrical System:**

12 Volt battery. Alternator, 13amp charging. Solenoid shift starter.

- Belts:** Kevlar cord. Self-adjusting, spring-loaded self-tightening
- Drive/Load Pulleys:** Split-steel design -- stronger and lighter weight than cast-iron
- Instrument Panel :** Key switch, throttle, manual choke, BBC switch
- Seat:** Adjustable, fully cushioned, molded seat.
- PTO - Electric Clutch:** Ogura GT2.5 - 175 ft lb / adjustable air-gap
- Cutter Decks:** 36" & 42" Advantage Decks. Floating, adjustable, anti-scalping design.
- Cutter Deck Construction:** Dual-Plate, welded with 10-gauge steel cutter deck top and 7-gauge upper support plate.
- Cutter Deck Drive:** Belt driven -- Straight belt for long life, not a twisted "mule" drive
- Number of Anti-Scalp Wheels:**
- 36": 2 rollers on rear of deck
  - 42": 2 rollers on rear of deck
- Cutter Deck Spindles:** Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty
- Cutter Deck Height Adjustment:**
- Foot pedal lift with self-locking mechanism at transport position
- Cutting Range:** 1-1/4" to 5-1/2" in 1/4" increments
- Number of Cutter Blades:** 3 Marbain blades
- Total Length:**
- 36" models: 72"
  - 42" models: 72"
- Total Width (with discharge chute in mowing position):**
- 36" models: 47"
  - 42" models: 53"
- Total Width (with discharge chute in transport position):**
- 36" models: 37"
  - 42" models: 43"
- Height (with ROPS):** 66-1/4"
- Height (with ROPS folded):** 53.5"
- Weight (with ROPS):**
- 36" models: 850 lbs.
  - 42" models: 860 lbs.
- Warranty:**
- 2 Yr. Mower Warranty—Parts & labor.
  - 3 Yr. Deck Warranty—First & second years parts & labor; third year parts.
  - 3 Yr. Spindle Warranty—First & second years parts & labor; third year parts.
  - 2 Yr. Engine Warranty—Minimum of a two-year warranty covered directly through the individual engine manufacturer.



All specifications subject to change without notice.

[WWW.SCAG.COM](http://WWW.SCAG.COM)